



TABLE-1

APPLICABLE CABLE WIRE			
	CONDUCTOR	AWG#24 STRANDED WIRE TO AWG#27 STRANDED WIRE	
	INSULATOR DIAMETER	φ0.9 TO φ1.0	
	JACKET DIAMETER	φ5.8 TO φ6.0	

- NOTES
- 1 APPLICABLE CABLE IS SHOWN IN TABLE-1.
 - 2. REFER TO HRS INSTRUCTION MANUAL(ETAD-E2847) FOR CABLE ASSEMBLING THAT MEETS CAT6a PERFORMANCE.
 - 3 COLORS ARE DIFFERENT DEPENDING ON THE SPECIFICATION NUMBER.

2	PHOSPHOR BRONZE	CONTACT:GOLD PLATING 1.27μm MIN LEAD :GOLD PLATING 0.03μm MIN UNDER :NICKEL PLATING 2μm MIN			
1	PHOSPHOR BRONZE	CONTACT:GOLD PLATING 1.27μm MIN LEAD :GOLD PLATING 0.03μm MIN UNDER :NICKEL PLATING 2μm MIN	4	POLYCARBONATE	YELLOW
			3	STAINLESS STEEL	OVER:NICKEL PLATING 0.5μm MIN
NO.	MATERIAL	FINISH . REMARKS	NO.	MATERIAL	FINISH . REMARKS
UNITS mm		SCALE 2 : 1	COUNT △	DESCRIPTION OF REVISIONS	
HRS HIROSE ELECTRIC CO., LTD.		APPROVED : NM. NISHIMATSU 14.06.26	DESIGNED	DRAWING NO. EDC3-126868-05	
		CHECKED : NM. NISHIMATSU 14.06.26	CHECKED	PART NO. TM31P-TM-88P(61)	
		DESIGNED : MT. ITANO 14.06.26	DATE	CODE NO. CL222-4626-7-61	
		DRAWN : MT. ITANO 14.06.26		△ 1/1	